

Cinecorder-TRANSPORTABLE

Digital Video-Assist System

Product Specification Sheet

01/06/00



Cinelogic[®]

17825 Osborne Street, Northridge, CA 91325
(818)772-4777 fax (818)772-4733 e-mail: cinelogic@videoassist.com

Specifications subject to change without notice.

'Windows 95, Windows 98' are registered Trademarks of Microsoft, Redmond

'Adobe Premiere' is a registered Trademark Adobe Inc., San Jose

'Cinelogic' is a registered Trademark of Sam Cheroff, Northridge

Cinecorder Transportable



The **Cinecorder TRANSPortable** Digital Video-Assist System is a computer for those customers that need a standardized transportable housing. The Cinecorder Portable uses a standard transportable ("Lunchbox" style) housing, which allows a wide range of configurations, and expansion. The co-polymer plastic outer skin surrounds an aluminum inner frame for strength and reduced weight.

The Cinecorder Transportable runs on standard AC power or an optional dual DC power supply. It can be equipped with up to four storage drives (one of these used for the Operating-System) which will give you 50+ hours of video recording time.

The size and shape of the Cinecorder Transportable makes it a good platform to add many interesting options, if so desired: CD or DVD recorders, removable hard drives & cartridge drives to name a few.

The Transportable can also be fitted with internally wired video and audio input and output connectors.


Technical Specifications

Computer System

Processor	PII400 – PIII700
Memory	128 MB
Capture-Card	Miro DC30pro (MJPEG, Compression between 15:1 up to 3.5:1)
System-Disc	1 – 10 GB IBM-Disc
Capture-Discs	2 – 25 GB IBM-Discs, upgradeable to 37 GB.
Monitor	LCD Monitor, 1024x768 Resolution
Keyboard	Full-Size Keyboard
Input-Device	Logitech Marble FX Trackball Infrared—Impervious to dirt

System Housing

Size	40 cm (15,8") W x 39cm (13") H x 34cm (9,2") D
Weight	17.5 Kg (38 lbs)
Housing	External high impact plastic shell with internal aluminum frame
Cooling	Three Internal Fans
Noise-Emission	Sound-Level is compatible with most shooting-situations
Power-Supply	Standard Power Supply Accepts DC 100-250 V or Internal DC Power Supply with two connectors. Hot Swappable. If Battery is connected while being connected to AC-Adaptor, it serves as an UPS.
Power-Consumption	100 Watts Max. (Nom. 5 Hours on a 30 Amp. Battery)
Temperature-Range	-10°C to 50°C (20°F to 120°F)



Cinellogic®

17825 Osborne Street, Northridge, CA 91325
(818)772-4777 fax (818)772-4733 e-mail: cinellogic@videoassist.com

Specifications subject to change without notice.
'Windows 95, Windows 98' are registered Trademarks of Microsoft, Redmond
'Adobe Premiere' is a registered Trademark Adobe Inc., San Jose